

ESD VINYL ROLL

PRODUCT INFORMATION

Item	Standard	Data
Size(m)	SJ/T11236-2001	20(Length) * 2(Width)
	EN427	
Thickness(mm)	SJ/T11236-2001	2.0
	EN428	
Weight(g/m ²)	SJ/T1123'6-2001	2900(2mm Thickness)
	EN430	
Dimensional	ASTM F2199:2009	≤0.40%
	EN 434	

TEST PARAMETER

Item	Standard	Data	
Electrical Resistance(Ω)	SJ/T11236-2001	Conductive: 10 ⁴ -10 ⁶ Ω Static-dissipative: 10 ⁶ -10 ⁹ Ω	
	EN1081		
Stating Voltage	SJ/T11236-2001	50V	100V
	AATCC-134	V < 100V	
Static Decay(s)	GJB2605-1996	≤2	
	FTM1080-4046	0.01	0.01
Fire Resistance	SJ/T11236-2001	FV-0	
	EN13501-1	Bfl-s1	
Slip Resistance Wet	DIN 51130	R9	
	EN13893	≥0.3	
Residual Concavity	SJ/T11236-2001	≤0.10	
	EN433	0.03	
Effect of Castor Chair	EN425	No delamination No cracks	
Formaldehyde Emission	EN717-1	None	
Color Fastness	ISO 105B 02	≥6	
Chemical Products Resistance	EN ISO 26987:2012	OK	
Toxic Texting	EN 71-3	OK	
	GB 18586-2001		
Smoke Production	GB8624-2006	≤750%,min	
Anti-bacterial	ISO 22196	Rate I	
Impact Sound Absorption	EN 0717/2	Approx 2dB	

